

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-11. (canceled)

12. (currently amended) A method for producing nitrogen fertilizer from organic waste products in the liquid phase and for hygienizing the wastes and reducing the emissions by thermal treatment using mineral or organic additions, characterized by that the waste product is heated ~~without the addition of chemicals such as acids or lyes~~ to temperatures between 40 and 90° C., while~~simultaneously~~ the pressure is first evacuated to 10 to 30 kPa, and then the pressure is increased to 40 to 80 kPa, without being accompanied by appreciable amounts of water, the escaping gas containing carbon dioxide and ammonia is cooled down and introduced into an aqueous absorption agent or brought into contact therewith, the nitrogen fertilizer formed thereby is discharged and the excess gas not having been absorbed and containing carbon dioxide is conducted back into the process, with maintenance of the temperature in the discharge container at a predetermined value, such that the underpressure between 10 and 80 kPa generated at the beginning of the process by a vacuum pump is autogenously maintained by the progress of the process, and the ammonium nitrogen is nearly fully removed.

13. (previously presented) A method according to claim 1, characterized by that the excess gas not having been absorbed and containing carbon dioxide is conducted back into the cycle by either

conducting it through the waste product to be treated, or
immediately above the waste product to be treated, or
through the gas cooling system above the waste product to be treated, or
dividing it and conducting a partial flow through the waste product and another partial flow above the waste product.

14. (previously presented) A method according to claim 1, characterized by that a temperature is adjusted in the front portion of the gas cooling system, which is at least 3 K and at most 15 K below the temperature in the stripping container, whereas in the rear part another cooling-down process to 40° C takes place.

15. (previously presented) A method according to claim 1, characterized by that to the excess gas conducted in the cycle, in addition carbon dioxide in a mixture with other gases is added from outside.

16. (previously presented) A method according to claim 1, characterized by that fermented manure is used as waste product, and that it is heated up to 70 to 85° C at a reduced pressure.

17. (previously presented) A method according to claim 5, characterized by that the fermented manure is filtered before its thermal vacuum treatment ~~in a per se known manner~~, and that the hygienized discharge manure formed after the thermal treatment is sprayed on meadows and fields as a virtually odorless sludge liquor stripped from nitrogen compounds, whereas the solid substances separated after filtration are composted.

18. (currently amended) A method according to claim 1, ~~wherein characterized by that~~
~~as~~ said aqueous absorption agent, a sulfate solution and/or a gypsum suspension
having a content of solid matter of 10% by mass to 50% by mass is used, and wherein
the latter is stirred in a collection container, and the product containing deposited lime
and ammonium sulfate is taken out from the container.

19. (withdrawn) A device for producing nitrogen fertilizer according to claim 1,
composed of the following essential parts:

- a stripping container for heating at underpressure,
- a collection container for a reaction in a heterogeneous phase,
- a heat storage for heat exchange,
- a vacuum pump,
- a heating water pump,
- a circulation fan,
- a stirrer,

in order to thus secure the circulation movement, and per se known pipelines, shutoff
devices, and measurement and control devices.

20. (withdrawn) A device for producing nitrogen fertilizer according to claim 8,
characterized by that the device comprises an additional gas cooling system with an
upwards directed separating column and a downwards directed cooler, and additional
pipelines and ball valves, in order that the circulating gas can be fed fully or partially into
the stripping container above the waste product, or through the cooling system into the
collection container, or partially into the stripping container into the waste product,
wherein the residual flows in case of a division of the circulating gas are optionally fed
into the two remaining designated entry positions.